

Vancore 

Worldwide Percussion

Product information
SNARE DRUMS



Corps Custom Economic Series

CORPS CUSTOM ECONOMIC SERIES SNAREDRUMS

Using high quality components, aluforce or Plywood Impact shells, CC machines aluminum rings, and a choice of snare strainer these snare drums are always on our production schedule. Economically designed with less material but keeping focus on quality

CORPS CUSTOM ECONOMIC SERIES | GREAT VALUE FOR LESS...!!

TENSION RODS

Using chrome plated tensionrod the drums can be tunes very easily




LUGS

The special shaped and high pressure diecasted Zamac twin lugs stand for pure quality an exclusive design . The lugs are fitted with bronze and chrome plated inserts. Inside the lugs you will find a special synthetic "locker" to hold the tension and avoid the rods to loosen their tension
The lugs are fitted to the shell using a special syntetic underlayment to avoid the contact with the shell.




SNARES

Top | Using wire snares (20 strands) the available snare systems stand for the most crispy and accurate sound available.
Bottom | Depending on model of strainer:
XS - 20 strands wiresnare high quality standard
UCS - 10 pieces of very accurate stainless steel cable snares



PROTECTION BRACKETS

To protect the different snarestrainers and tensionhoops when putting the drum on the floor, a set of 2 solid chrome plated brackets are mounted on the drum.



DRUMHEADS

We only use the best component and there fore these series we choosed for Reno Ambassador as a standard but optional you can choose for White Max or Cybermax drumhead.

Top | Remo Ambassador

Bottom | Depending on snarestrainer
XS: Remo Ambassador TD
UCS: Remo Ambassador SA



"THE BEST DRUMS NEED ONLY THE BEST AVAILABLE DRUMHEADS"

TENSIONRINGS

Made out of special aluminium alloy. Focused on strength and durability. Precisely CC machined, mirror finished and available in different finishes.
Just the best quality available on the entire market



TOP STRAINER

Easy to handle and fully adjustable, both height and snare tensioning. CC machined components like Delrin and special high quality anodized aluminium completes the strainer are the absolute top level available. Reliable and functional for the extreme demands in sound and function.



BOTTOM STRAINER | Three different models to choose from

XS STRAINER | The External Strainer is made out of high quality components, and completely CC Machined. The mechanism works outside the shell. No internal material is uses inside the shell. The shell can just do where it is made for! The XS snarestrainer is fully adjustable in both height and snare tension. Beside that the height of the strainer can be fully compensates when you tension up the bottom tension ring. Of course CC technology is used in manufacturing this excellent strainer.



UCS STRAINER | The biggest innovation insnardrum tecnogy!! Made out of special designed extrusion profiles precisely CC machine tuned.
This ultimate strainer gives the snare drummer the comfort of shifting the strainer during his playing activities. Besides a technical high standard it gives an ultimate in musical performance!!!
Tension and height of the snares are fully adjustable.
The one and only on the entire market.



CORPS CUSTOM ECONOMIC SERIES | GREAT VALUE FOR LESS....!

SHELLS



Plywood Impact | A 4mm 6-ply wooden shell made out of a combination of beech and occume. Both wood species which are the basics of light and strong drums shell.

PLYWOOD IMPACT | THE HEARTBEAT OF YOUR DRUM!!

Aluforce | Precisely CC bended and welded aluminium shells made out of a special 1.5 mm aluminium sheet material. Extremely light in weight with an excellent performance in sound and durability.

ALUFORCE IT JUST SAYS WHERE IT STANDS FOR!!
LIGHT IN WEIGHT AND STRONG IN SOUND!!



COLOR OPTIONS

“Various Shell and Hardware colour finishes available, please ask for colour charts!”



FEATURES AND MODELS



Art. nr.	Size	Shell	Tensionrings	Lugs	Strainer	Top Wire	Bot- tom Wire	Ten- sion Rods	Drumheads	Weight
CES1206SO08	12" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	3.7 kg 8.2 lbs
CES1210SO08	12" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.2 kg 9.3 lbs
CES1306SO08	13" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	3.8 kg 8.4 lbs
CES1310SO08	13" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.3 kg 9.5 lbs
CES1406SO08	14" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.1 kg 9.1 lbs
CES1410SO08	14" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.8 kg 10.5 lbs
CES1412SO08	14" x 12"	Plywood Impact	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	5.0 kg 11.0 lbs
CES1406XS08	14" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	XS		Steel Wires	8	Remo Amb. Smooth White	4.6 kg 10.2 lbs
CES1410XS08	14" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	XS		Steel Wires	8	Remo Amb. Smooth White	5.3 kg 11.6 lbs
CES1412XS08	14" x 12"	Plywood Impact	CC Machined High Grade Aluminum	8	XS		Steel Wires	8	Remo Amb. Smooth White	5.5 kg 12.1 lbs
CES1406XS/TS08	14" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	XS/TS	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	5.4 kg 11.9 lbs
CES1410XS/TS08	14" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	XS/TS	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	6.0 kg 13.3 lbs
CES1412XS/TS08	14" x 12"	Plywood Impact	CC Machined High Grade Aluminum	8	XS/TS	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	6.3 kg 13.8 kg
CES1206UCS08	12" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.5 kg 10.0 lbs
CES1210UCS08	12" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	5.0 kg 11.1lbs
CES1306UCS08	13" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.6 kg 10.1 lbs
CES1310UCS08	13" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	5.1 kg 11.2 lbs
CES1406UCS08	14" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.6 kg 10.2 lbs
CES1410UCS08	14" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	5.3 kg 11.6 lbs
CES1412UCS08	14" x 12"	Plywood Impact	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	5.5 kg 12.1 lbs
CES1406UCT08	14" x 6,5"	Plywood Impact	CC Machined High Grade Aluminum	8	UCT	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	5.4 kg 11.9 lbs
CES1410UCT08	14" x 10"	Plywood Impact	CC Machined High Grade Aluminum	8	UCT	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	6.0 kg 13.3 lbs
CES1412UCT08	14" x 12"	Plywood Impact	CC Machined High Grade Aluminum	8	UCT	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	6.3 kg 13.8 lbs

FEATURES AND MODELS



Art. nr.	Size	Shell	Tensionrings	Lugs	Strainer	Top Wire	Bot- tom Wire	Ten- sion Rods	Drumheads	Weight
ATS1206SO08E	12" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	3.5 kg 7.7 lbs
ATS1210SO08E	12" x 10"	Aluforce	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.0 kg 8.8 lbs
ATS1306SO08E	13" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	3.5 kg 7.8 lbs
ATS1310SO08E	13" x 10"	Aluforce	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.0 kg 8.9 lbs
ATS1406SO08E	14" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	3.9 kg 8.5 lbs
ATS1410SO08E	14" x 10"	Aluforce	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.5 kg 9.9 lbs
ATS1412SO08E	14" x 12"	Aluforce	CC Machined High Grade Aluminum	8	SO		Steel Wires	8	Remo Amb. Smooth White	4.8 kg 10.5 lbs
ATS1406XS08	14" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	XS		Steel Wires	8	Remo Amb. Smooth White	4.4 kg 9.6 lbs
ATS1410XS08	14" x 10"	Aluforce	CC Machined High Grade Aluminum	8	XS		Steel Wires	8	Remo Amb. Smooth White	5.0 kg 11.0 lbs
ATS1412XS08	14" x 12"	Aluforce	CC Machined High Grade Aluminum	8	XS		Steel Wires	8	Remo Amb. Smooth White	5.3 kg 11.6 lbs
ATS1406XS/TS08	14" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	XS/TS	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	5.1 kg 11.3 lbs
ATS1410XS/TS08	14" x 10"	Aluforce	CC Machined High Grade Aluminum	8	XS/TS	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	5.8 kg 12.7 lbs
ATS1412XS/TS08	14" x 12"	Aluforce	CC Machined High Grade Aluminum	8	XS/TS	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	6.0 kg 13.3 kg
ATS1206UCS08	12" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.3 kg 9.5 lbs
ATS1210UCS08	12" x 10"	Aluforce	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.8 kg 10.6 lbs
ATS1306UCS08	13" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.3 kg 9.5 lbs
ATS1310UCS08	13" x 10"	Aluforce	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.8 kg 10.6 lbs
ATS1406UCS08	14" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	4.4 kg 9.6 lbs
ATS1410UCS08	14" x 10"	Aluforce	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	5.0 kg 11.0 lbs
ATS1412UCS08	14" x 12"	Aluforce	CC Machined High Grade Aluminum	8	UCS		Cable Wires	8	Remo Amb. Smooth White	5.3 kg 11.6 lbs
ATS1406UCT08	14" x 6,5"	Aluforce	CC Machined High Grade Aluminum	8	UCT	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	5.1 kg 11.3 lbs
ATS1410UCT08	14" x 10"	Aluforce	CC Machined High Grade Aluminum	8	UCT	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	5.8 kg 12.7 lbs
ATS1412UCT08	14" x 12"	Aluforce	CC Machined High Grade Aluminum	8	UCT	Steel Wires	Steel Wires	8	Remo Amb. Smooth White	6.0 kg 13.3 lbs

Vancore Nederland b.v.
 Tolhuswei 7a - 9
 8501 ZP JOURE - The Netherlands
 Tel: +31 513 415127
 Fax: +31 513 413038
 Email: info@vancore.nl

WWW.VANCORE.COM