

Vancore 

Worldwide Percussion

Product Information

TOMSETS



| Corps Custom Lite Series |

CORPS CUSTOM LITE SERIES TOMSETS

These tenorsets are available in different set ups. We choosed carrefully the leightweight materials especially for the younger tenor players.

Easy to carry as result of differents the set ups and the leightweight instruments.

CORPS CUSTOM LITE SERIES | DESIGNED FOR THE YOUNG MARCHINGDRUMMERS!

Lite in weight great in sound!!

TENSION RODS

Using chrome plated tensionrod the drums can be tuned very easily The tenors are fitted with different numbers of lugs and tensionrods for optimal tuning See technical specs

DRUMHEADS

We only use the best component and there fore these series we choose for Remo Ambassador Clear heads for excellent projection and endurance.

"THE BEST DRUMS NEED ONLY THE BEST AVAILABLE DRUMHEADS"

LUGS

We choose carefully the light weight lugs for this series

| | |
|-----|--------|
| 6" | 4 lugs |
| 8" | 4 lugs |
| 10" | 6 lugs |
| 12" | 6 lugs |
| 13" | 6 lugs |

TENSIONRINGS

The tripple flanged and 2.3. mm tensionhoops will stand the tension you need.

CORPS CUSTOM LITE TOMSET | LIGHT IN WEIGHT GREAT IN SOUND!

SHELLS



Plywood Impact | A 6mm 6-ply wooden shell made out of a combination of beech and occume. Both wood species which are the basics of light and strong drums shell. Available in standard and power version.

PLYWOOD IMPACT | THE HEARTBEAT OF YOUR DRUM!!

Aluforce | Precisely CC bended and welded aluminium shells made out of a special 1.5 mm aluminium sheet material. Extremely light in weight with an excellent performance in sound and durability.

**ALUFORCE IT JUST SAYS WHERE IT STANDS FOR!!
LIGHT IN WEIGHT AND STRONG IN SOUND!!**



COLOR OPTIONS

“Various Shell and Hardware colour finishes available, please ask for colour charts!”



FEATURES AND MODELS



| Art. nr. | Size | Shell | Tension-rings | Lugs | Tension Rods | Drumheads | Weight |
|----------|----------------------|----------------|---------------|-------------|--------------|-----------------------|--------------------|
| CTL301S | 6"/8"/10" | Plywood Impact | 2.3 mm steel | 4/4/6 | 4/4/6 | Remo Ambassador Clear | 4.3 kg 9.4 lbs |
| CTL302S | 8"/10"/12" | Plywood Impact | 2.3 mm steel | 4/6/6 | 4/6/6 | Remo Ambassador Clear | 4.8 kg 10.7 lbs |
| CTL303S | 10"/12"/13" | Plywood Impact | 2.3 mm steel | 6/6/6 | 6/6/6 | Remo Ambassador Clear | 5.2 kg 11.4 lbs |
| CTL401S | 6"/8"/10"/12" | Plywood Impact | 2.3 mm steel | 4/4/6/6 | 4/4/6/6 | Remo Ambassador Clear | 5.7 kg 12.5 lbs |
| CTL402S | 8"/10"/12"/13" | Plywood Impact | 2.3 mm steel | 4/6/6/6 | 4/6/6/6 | Remo Ambassador Clear | 6.3 kg 13.9 lbs |
| CTL501S | 6"/6"/8"/10"/12" | Plywood Impact | 2.3 mm steel | 4/4/4/6/6 | 4/4/4/6/6 | Remo Ambassador Clear | 6.7 kg 14.7 lbs |
| CTL601S | 6"/6"/8"/10"/12"/13" | Plywood Impact | 2.3 mm steel | 4/4/4/6/6/6 | 4/4/4/6/6/6 | Remo Ambassador Clear | 8.2 kg 18.2 lbs |



| Art. nr. | Size | Shell | Tension-rings | Lugs | Tension Rods | Drumheads | Weight |
|----------|----------------------|----------|---------------|-------------|--------------|-----------------------|--------------------|
| ATT301L | 6"/8"/10" | Aluforce | 2.3 mm steel | 4/4/6 | 4/4/6 | Remo Ambassador Clear | 4.4 kg 9.7 lbs |
| ATT302L | 8"/10"/12" | Aluforce | 2.3 mm steel | 4/6/6 | 4/6/6 | Remo Ambassador Clear | 5.1 kg 11.2 lbs |
| ATT303L | 10"/12"/13" | Aluforce | 2.3 mm steel | 6/6/6 | 6/6/6 | Remo Ambassador Clear | 5.4 kg 11.9 lbs |
| ATT401L | 6"/8"/10"/12" | Aluforce | 2.3 mm steel | 4/4/6/6 | 4/4/6/6 | Remo Ambassador Clear | 5.9 kg 13.1 lbs |
| ATT402L | 8"/10"/12"/13" | Aluforce | 2.3 mm steel | 4/6/6/6 | 4/6/6/6 | Remo Ambassador Clear | 6.6 kg 14.5 lbs |
| ATT501L | 6"/6"/8"/10"/12" | Aluforce | 2.3 mm steel | 4/4/4/6/6 | 4/4/4/6/6 | Remo Ambassador Clear | 6.9 kg 15.3 lbs |
| ATT601L | 6"/6"/8"/10"/12"/13" | Aluforce | 2.3 mm steel | 4/4/4/6/6/6 | 4/4/4/6/6/6 | Remo Ambassador Clear | 8.4 kg 18.5 lbs |



Vancore Nederland b.v.

Tolhuswei 7a - 9

8501 ZP JOURE - The Netherlands

Tel: +31 513 415127

Fax: +31 513 413038

Email: info@vancore.nl

WWW.VANCORE.COM